

FortiGate® Network Security Platform - *Top Selling Models Matrix

	FG/FWF-40F	FG/FWF-60F	FG-70F	FG/FWF-80F
Firewall Throughput (1518/512/64 byte UDP)	5 / 5 / 5 Gbps	10/10/6 Gbps	10 / 10 / 6 Gbps	10 / 10 / 7 Gbps
IPsec VPN Throughput (512 byte) ¹	4.4 Gbps	6.5 Gbps	6.1 Gbps	6.5 Gbps
IPS Throughput (Enterprise Mix) ²	1 Gbps	1.4 Gbps	1.4 Gbps	1.4 Gbps
NGFW Throughput (Enterprise Mix) ^{2,4}	800 Mbps	1 Gbps	1 Gbps	1 Gbps
Threat Protection Throughput (Ent. Mix) ^{2,5}	600 Mbps	700 Mbps	800 Mbps	900 Mbps ⁶
Firewall Latency	2.97 µs	3.3 µs	2.54 µs	3.23 µs
Concurrent Sessions	700,000	700,000	1.5 Million	1.5 Million
New Sessions/Sec	35,000	35,000	35,000	45,000
Firewall Policies	5,000	5,000	5,000	5,000
Max G/W to G/W IPSEC Tunnels	200	200	200	200
Max Client to G/W IPSEC Tunnels	250	500	500	2,500
SSL VPN Throughput	490 Mbps	900 Mbps	405 Mbps ⁹	950 Mbps
Concurrent SSL VPN Users (Recommended Maximum, Tunnel Mode)	200	200	200	200
SSL Inspection Throughput (IPS, avg. HTTPS) ³	310 Mbps	630 Mbps	700 Mbps	715 Mbps
Application Control Throughput (HTTP 64K) ²	990 Mbps	1.8 Gbps	1.8 Gbps	1.8 Gbps
Max FortiAPs (Total / Tunnel)	16 / 8	64 / 32	64 / 32	96 / 48
Max FortiSwitches	8	16	16	16
Max FortiTokens	500	500	500	500
Virtual Domains (Default/Max)	10 / 10	10 / 10	10 / 10	10 / 10

Interfaces	5x GE RJ45	10x GE RJ45	10x GE RJ45	8x GE RJ45, 2x Shared Port Pairs
Local Storage	—	128 GB (61F)	128 GB (71F)	128 GB (81F)
Power Supplies	Single AC PS	Single AC PS	Single AC PS	Single AC PS, dual inputs
Form Factor	Desktop	Desktop	Desktop	Desktop
Variants	WiFi, 3G4G	WiFi, Storage	—	WiFi, 3G4G, DSL, Bypass, Storage

	FG-100F	FG-200F	FG-400E	FG-600F
Firewall Throughput (1518/512/64 byte UDP)	20 / 18 / 10 Gbps	27 / 27 / 11 Gbps	32 / 32 / 24 Gbps	139 / 137.5 / 70 Gbps
IPsec VPN Throughput (512 byte) ¹	11.5 Gbps	13 Gbps	20 Gbps	55 Gbps
IPS Throughput (Enterprise Mix) ²	2.6 Gbps	5 Gbps	7.8 Gbps	14 Gbps
NGFW Throughput (Enterprise Mix) ^{2,4}	1.6 Gbps	3.5 Gbps	6 Gbps	11.5 Gbps
Threat Protection Throughput (Ent. Mix) ^{2,5}	1 Gbps	3 Gbps	5 Gbps	10.5 Gbps
Firewall Latency	4.97µs	4.78 µs	2.14 µs	4.12 µs
Concurrent Sessions	1.5 Million	3 Million	4 Million	8 Million
New Sessions/Sec	56,000	280,000	450,000	550,000
Firewall Policies	10,000	10,000	10,000	10,000
Max G/W to G/W IPSEC Tunnels	2,000	2,000	2,000	2,000
Max Client to G/W IPSEC Tunnels	16,000	16,000	50,000	50,000
SSL VPN Throughput	1 Gbps	2 Gbps	4.5 Gbps	4.3 Gbps ⁹
Concurrent SSL VPN Users (Recommended Maximum, Tunnel Mode)	500	500	5,000	10,000
SSL Inspection Throughput (IPS, avg. HTTPS) ³	1 Gbps	4 Gbps	4.8 Gbps	9 Gbps
Application Control Throughput (HTTP 64K) ²	2.2 Gbps	13 Gbps	12 Gbps	32 Gbps
Max FortiAPs (Total / Tunnel)	128 / 64	256 / 128	512 / 256	1024 / 512
Max FortiSwitches	32	64	72	96
Max FortiTokens	5,000	5,000	5,000	5,000
Virtual Domains (Default/Max)	10 / 10	10 / 10	10 / 10	10 / 10

Interfaces	2x 10 GE SFP+, 18x GE RJ45, 4x Shared Port Pairs, 8x GE SFP	4x 10 GE SFP+, 18x GE RJ45, 8x GE SFP	18x GE RJ45, 16x GE SFP	4x 25G SFP28, 4x 10GE SFP+, 18 x GE RJ45
Local Storage	480 GB (101F)	480 GB (201F)	480 GB (401E)	480 GB (601F)
Power Supplies	Dual AC PS	Dual AC PS	Single AC PS, opt. Dual PS	Dual AC PS
Form Factor	1 RU	1 RU	1 RU	1 RU
Variants	—	—	—	—

FortiGate® Network Security Platform - *Top Selling Models Matrix

	FG-1100E	FG-1800F	FG-2200E	FG-2600F
Firewall Throughput (1518/512/64 byte UDP)	80 / 80 / 45 Gbps	198 / 197 / 140 Gbps	158 / 155 / 100 Gbps	198 / 196 / 120 Gbps
IPsec VPN Throughput (512 byte) ¹	48 Gbps	55 Gbps	98 Gbps	55 Gbps
IPS Throughput (Enterprise Mix) ²	12.5 Gbps	17 Gbps	21 Gbps	24 Gbps
NGFW Throughput (Enterprise Mix) ^{2,4}	9.8 Gbps	11 Gbps	13.5 Gbps	19 Gbps
Threat Protection Throughput (Ent. Mix) ^{2,5}	7.1 Gbps	9.1 Gbps	11 Gbps	17 Gbps
Firewall Latency	2.76 µs	3.22 µs	3.09 µs	3.41 µs
Concurrent Sessions	8 Million	12 Million / 40 Million ⁷	24 Million	24 Million / 40 Million ⁷
New Sessions/Sec	500,000	750,000 / 2 Million ⁷	500,000	1 Million / 2 Million ⁷
Firewall Policies	100,000	100,000	100,000	100,000
Max G/W to G/W IPSEC Tunnels	20,000	20,000	20,000	20,000
Max Client to G/W IPSEC Tunnels	100,000	100,000	100,000	100,000
SSL VPN Throughput	8.4 Gbps	11 Gbps	10 Gbps	16 Gbps
Concurrent SSL VPN Users (Recommended Maximum, Tunnel Mode)	10,000	10,000	30,000	30,000
SSL Inspection Throughput (IPS, avg. HTTPS) ³	10 Gbps	12 Gbps	17 Gbps	20 Gbps
Application Control Throughput (HTTP 64K) ²	26 Gbps	34 Gbps	52 Gbps	64 Gbps
Max FortiAPs (Total, Tunnel)	4,096 / 2,048	4,096 / 2,048	4,096 / 2,048	4,096 / 2,048
Max FortiSwitches	196	196	196	196
Max FortiTokens	20,000	20,000	20,000	20,000
Virtual Domains (Default/Max)	10 / 250	10 / 250	10 / 500	10 / 500
Interfaces	2× 40GE QSFP+, 4× 25GE SFP28, 4× 10GE SFP+, 8× GE SFP, 18× GE RJ45	4× 40 GE QSFP+, 12× 25 GE SFP28, 2×10 GE SFP+, 8× GE SFP, 18× GE RJ45	4× 40GE QSFP+, 20× 25GE SFP28, 14× GE RJ45	4× 100GE QSFP28/40GE QSFP+, 16× 25GE SFP28, 16× 10GE RJ45, 2× 10GE SFP+, 2x GE RJ45
Local Storage	960 GB (1101E)	2 TB (1801F)	2 TB (2201E)	2 TB (2601F)
Power Supplies	Dual PS	Dual PS	Dual PS	Dual PS
Form Factor	2 RU	2 RU	2 RU	2 RU
Variants	DC	DC	—	DC
	FG-3000F	FG-3300E	FG-3400E	FG-3500F
Firewall Throughput (1518/512/64 byte UDP)	397 / 389 / 221 Gbps	160 / 158 / 100 Gbps	240 / 238 / 150 Gbps	595 / 590 / 420 Gbps
IPsec VPN Throughput (512 byte) ¹	105 Gbps	98 Gbps	140 Gbps	165 Gbps
IPS Throughput (Enterprise Mix) ²	36 Gbps	27 Gbps	44 Gbps	72 Gbps
NGFW Throughput (Enterprise Mix) ^{2,4}	34 Gbps	23 Gbps	34 Gbps	65 Gbps
Threat Protection Throughput (Ent. Mix) ^{2,5}	33 Gbps	17 Gbps	25 Gbps	63 Gbps
Firewall Latency	3.92 µs	3.17 µs	3.33 µs	2.98 µs
Concurrent Sessions	70 Million / 230 Million ⁷	50 Million	50 Million	140 Million / 348 Million ⁷
New Sessions/Sec	870 000 / 3 Million ⁷	700,000	850,000	1 Million / 5 Million ⁷
Firewall Policies	200,000	200,000	200,000	200,000
Max G/W to G/W IPSEC Tunnels	40,000	40,000	40,000	40,000
Max Client to G/W IPSEC Tunnels	200,000	200,000	200,000	200,000
SSL VPN Throughput	11 Gbps ⁹	10 Gbps	11 Gbps	16 Gbps ⁹
Concurrent SSL VPN Users (Recommended Maximum, Tunnel Mode)	30,000	30,000	30,000	30,000
SSL Inspection Throughput (IPS, avg. HTTPS) ³	29 Gbps	21 Gbps	30 Gbps	63 Gbps
Application Control Throughput (HTTP 64K) ²	115 Gbps	70 Gbps	86 Gbps	135 Gbps
Max FortiAPs (Total, Tunnel)	4,096 / 2,048	4,096 / 2,048	4,096 / 2,048	4,096 / 2,048
Max FortiSwitches	300	300	300	300
Max FortiTokens	20,000	20,000	20,000	20,000
Virtual Domains (Default/Max)	10 / 500	10 / 500	10 / 500	10 / 500
Interfaces	6× 100GE QSFP28/40GE QSFP+, 16× 25GE SFP28, 18× 10GE RJ45, 2x GE RJ45	4× 40GE QSFP+, 16× 25GE SFP28, 4× 10GE RJ45, 14× GE RJ45	4× 100GE QSFP28/40GE QSFP+, 24× 25GE SFP28, 2x GE RJ45	6× 100GE QSFP28/40GE QSFP+, 32× 25GE SFP28, 2x GE RJ45
Local Storage	2 TB (3001F)	2 TB (3301E)	4 TB (3401E)	4 TB (3501F)
Power Supplies	Dual PS	Dual PS	Dual PS	Dual PS
Form Factor	2 RU	2 RU	2 RU	2 RU
Variants	—	—	DC	—

* Featured Top selling models, for complete FortiGate offerings please visit www.fortinet.com. FortiGate virtual appliances are also available. All performance values are “up to” and vary depending on system configuration.



FortiGate® Network Security Platform - *Top Selling Models Matrix

	FG-3600E	FG-3700F	FG-3960E	FG-3980E	FG-4200F
Firewall Throughput (1518/512/64 byte UDP)	240 / 240 / 150 Gbps	589 / 589 / 420 Gbps	620 / 610 / 370 Gbps	1.05 Tbps / 1.05 Tbps / 680 Gbps	800 / 788 / 400 Gbps
IPsec VPN Throughput (512 byte) ¹	140 Gbps	160 Gbps	280 Gbps	400 Gbps	210 Gbps
IPS Throughput (Enterprise Mix) ²	55 Gbps	86 Gbps	30 Gbps	32 Gbps	52 Gbps
NGFW Throughput (Enterprise Mix) ^{2,4}	40 Gbps	80 Gbps	22 Gbps	28 Gbps	47 Gbps
Threat Protection Throughput (Ent. Mix) ^{2,5}	30 Gbps	75 Gbps	13.5 Gbps	20 Gbps	45 Gbps ⁶
Firewall Latency	3.27µs	3.56 µs / 1.45 µs ⁸	3 µs	3 µs	3.02 µs
Concurrent Sessions	50 Million	140 Million	160 Million	160 Million	210 Million / 450 Million ⁷
New Sessions/Sec	950,000	930,000	720,000	800,000	1 Million / 7 Million ⁷
Firewall Policies	200,000	200,000	200,000	200,000	200,000
Max G/W to G/W IPSEC Tunnels	40,000	40,000	40,000	40,000	40,000
Max Client to G/W IPSEC Tunnels	200,000	200,000	200,000	200,000	200,000
SSL VPN Throughput	12 Gbps	16 Gbps ⁹	9 Gbps	9.5 Gbps	16 Gbps
Concurrent SSL VPN Users (Recommended Maximum, Tunnel Mode)	30,000	30,000	30,000	30,000	30,000
SSL Inspection Throughput (IPS, avg. HTTPS) ³	34 Gbps	55 Gbps	23 Gbps	26 Gbps	50 Gbps
Application Control Throughput (HTTP 64K) ²	95 Gbps	190 Gbps	40 Gbps	55 Gbps	135 Gbps
Max FortiAPs (Total, Tunnel)	4,096 / 2,048	4,096 / 2,048	8,192 / 4,096	8,192 / 4,096	8,192 / 4,096
Max FortiSwitches	300	300	300	300	300
Max FortiTokens	20,000	20,000	20,000	20,000	20,000
Virtual Domains (Default/Max)	10 / 500	10 / 500	10 / 500	10 / 500	10 / 500
Interfaces	6× 100GE QSFP28/40GE QSFP+, 32× 25GE SFP28, 2x GE RJ45	4× 400GE QSFP-DD, 4x ULL 25GE SFP28, 20x 50GE SFP56, 2x 10GE RJ45	6× 100GE QSFP28/40GE QSFP+, 16× 10GE SFP+, 2x GE RJ45	10× 100GE QSFP28/40GE QSFP+, 16× 10GE SFP+, 2x GE RJ45	8× 100GE QSFP28/40GE QSFP+, 18× 25GE SFP28, 2x GE RJ45
Local Storage	4 TB (3601E)	4 TB (3701E)	—	—	4 TB (4201F)
Power Supplies	Dual PS	Dual PS	3 PS	3 PS	Dual PS
Form Factor	2 RU	2 RU	5 RU	5 RU	3 RU
Variants	DC	—	DC	DC	DC

	FG-4400F	FG-6300F	FG-6500F	FG-7060E	FG-7121F/-2
Firewall Throughput (1518/512/64 byte UDP)	1.15 / 1.14 / 0.50 Tbps	239 / 238 / 135 Gbps	239 / 238 / 135 Gbps	630 / 630 / 340 Gbps	1.89 / 1.88 / 1.129 Tbps
IPsec VPN Throughput (512 byte) ¹	310 Gbps	96 Gbps	160 Gbps	100 Gbps	630 Gbps
IPS Throughput (Enterprise Mix) ²	94 Gbps	110 Gbps	170 Gbps	200 Gbps	675 Gbps
NGFW Throughput (Enterprise Mix) ^{2,4}	82 Gbps	90 Gbps	150 Gbps	120 Gbps	550 Gbps
Threat Protection Throughput (Ent. Mix) ^{2,5}	75 Gbps ⁶	60 Gbps	100 Gbps	96 Gbps	520 Gbps
Firewall Latency	2.98 µs	5 µs	5 µs	7 µs	7.5 µs
Concurrent Sessions	210 Million / 700 Million ⁷	120 Million	200 Million	320 Million	1 Billion
New Sessions/Sec	1 Million / 10 Million ⁷	2 Million	3 Million	1.8 Million	9 Million
Firewall Policies	200,000	200,000	200,000	200,000	200,000
Max G/W to G/W IPSEC Tunnels	40,000	16,000	16,000	16,000	40,000
Max Client to G/W IPSEC Tunnels	200,000	90,000	90,000	64,000	260,000
SSL VPN Throughput	16 Gbps	9 Gbps	9 Gbps	15 Gbps	13.7 Gbps
Concurrent SSL VPN Users (Recommended Maximum, Tunnel Mode)	30,000	30,000	30,000	48,000	30,000
SSL Inspection Throughput (IPS, avg. HTTPS) ³	86 Gbps	66 Gbps	110 Gbps	79.9 Gbps	540 Gbps
Application Control Throughput (HTTP 64K) ²	140 Gbps	150 Gbps	220 Gbps	160 Gbps	1.5 Tbps
Max FortiAPs (Total, Tunnel)	8,192 / 4,096	—	—	—	—
Max FortiSwitches	300	256	256	256	300
Max FortiTokens	20,000	20,000	20,000	20,000	20,000
Virtual Domains (Default/Max)	10 / 500	10 / 500	10 / 500	10 / 500	10 / 500
Interfaces	12× 100GE QSFP28/40GE QSFP+, 20× 25GE SFP28, 2x GE RJ45	4× 100GE QSFP28/40GE QSFP+, 24× 25GE SFP28, 3× 10GE SFP+, 2x GE RJ45	4× 100GE QSFP28/40GE QSFP+, 24× 25GE SFP28, 3× 10GE SFP+, 2x GE RJ45	Varied	Varied
Local Storage	4 TB (4401F)	2 TB NVMe (6301F)	2 TB NVMe (6501F)	—	4× 4 TB SSD
Power Supplies	4 PS	3 PS	3 PS	4+2 PS	8 PS
Form Factor	4 RU	3 RU	3 RU	8 RU	16 RU
Variants	DC	DC	DC	DC	DC

1. IPsec VPN performance test uses AES256-SHA256.

2. IPS, Application Control, NGFW and Threat Protection are measured with Logging enabled.

3. SSL Inspection performance values use an average of HTTPS sessions of different cipher suites.

4. NGFW performance is measured with Firewall, IPS and Application Control enabled, Enterprise Mix traffic.

5. Threat Protection performance is measured with Firewall, IPS, Application Control, (6.URL Filtering) and Malware Protection enabled, Enterprise Mix traffic.

7. Requires Hyperscale license

8. With Ultra-Low Latency ports

9. Uses RSA-2048 certificate



FortiManager™ Centralized Management Platform

	FMG-200G	FMG-300F	FMG-400G	FMG-1000F	FMG-2000E	FMG-3000G	FMG-3700G	FMG-VM-BASE to FMG-VM-UL-UG
Devices/VDOMs (Maximum)	30	100	150	1,000	1,200	4,000+	10,000+	10 to Unlimited
Sustained Log Rates	50	50	50	50	50	150	150	Hardware dependent
GB/Day	2	2	2	2	2	10	10	1-50
Total Interfaces	4x GE RJ45	4x GE RJ45, 2x GE SFP	4x GE RJ45, 2x GE SFP	2x GE RJ45, 2x 10GE SFP+	4x GE RJ45, 2x 10GE SFP+	2x GE RJ45, 2x 25GE SFP28	2x 10GE RJ45, 2x 25GE SFP28	1 / 4 (vNIC Min / Max)
Storage Capacity	2x 4 TB	4x 4 TB	8x 4 TB	8x 4 TB	12x 3 TB	16x 4 TB	60x 4TB HDD + 6x 3.2TB NVMe SSD	80 GB / 16 TB (Min / Max)

FortiAnalyzer™ Centralized Logging and Reporting Solution

	FAZ-150G	FAZ-300G	FAZ-800G	FAZ-1000F	FAZ-3000G	FAZ-3500G	FAZ-3700G	FAZ-VM-BASE to FAZ-VM-GB2000
GB Logs/Day	25	100	200	660	3,000	5,000	8,300	1 to +2,000
Analytic Sustained Rate (logs/sec)	500	2,000	4,000	20,000	42,000	60,000	100,000	—
Collector Sustained Rate (logs/sec)	750	3,000	6,000	30,000	60,000	90,000	150,000	—
Total Interfaces	2x GE RJ45	4x GE RJ45	4x GE RJ45, 2x GE SFP	2x GE RJ45, 2x 10GE SFP+	2x GE RJ45, 2x 25GE SFP28	2x GE RJ45, 2x 25GE SFP28	2x 10GE RJ45, 2x 25GE SFP28	1 / 4 (vNIC Min / Max)
Storage Capacity	2x 2 TB	2x 4 TB	4x 4 TB	8x 4 TB	16x 4 TB	24x 4 TB	60x 4TB HDD + 6x 3.2TB NVMe SSD	500 GB to +100 TB

FortiSIEM™ Unified Event Correlation and Risk Management Solution

	FSM-500G "COLLECTOR"	FSM-2000G "SUPERVISOR"	FSM-3500G "SUPERVISOR"
All-in-One License Capacity	N/A	Up to 500	Up to 2,000
EPS Capacity (all features enabled)	5,000	Up to 20,000	Up to 40,000

FortiAuthenticator™ User Identity Management Server

	FAC-300F	FAC-800F	FAC-3000F	FAC-VM BASE to FAC-VM-10000-UG
Max Local + Remote Users/ User Group	1,500 / 150	8,000 / 800	40,000 / 240,000	100 / 10 to +10,000 / 1,000
Max NAS Devices	500	2,666	80,000	33 to +33,333
Max FortiTokens	3,000	16,000	480,000	200 to +20,000
Interfaces	4x GE RJ45	4x GE RJ45, 2x SFP	4x GE RJ45, 2x SFP	1 - 4 vNICs
Storage Capacity	2	2x 2 TB	2x 2 TB	60 GB to 16 TB

FortiAP™ Wireless Access Point

	FortiAP Series	FortiAP U-Series
Management	FortiGate-Managed, Cloud-Managed	FortiGate-Managed, Cloud-Managed, Controller-Managed
Security	Via FortiGate	Via FortiGate

* Frequency selection and power may be restricted to abide by regional regulatory compliance laws.
For Complete selection of FortiAPs, including remote and outdoor devices, please refer to Fortinet Wireless Solution Matrix

FortiSwitch™ Secured Access Switch

	100 Series	200 Series	400 Series	500 Series	1000 Series	3000 Series
Main Port Speed	1 Gbps	1 Gbps	1 Gbps	1 Gbps	10/40 Gbps	40/100 Gbps
Main Port Count Options	8, 24, 48	24, 48	24, 48	24, 48	24, 48	32
Uplink Port Speed	1 or 10 Gbps	1 Gbps	10 Gbps	10 Gbps	40 or 100 Gbps	n/a
Redundant Power Supplies	—	Some Models	Some Models	Optional RSU	•	•
PoE Options	•	•	•	•	—	—

For Complete selection of FortiSwitches, please refer to <http://www.fortinet.com/products/fortiswitch>



FortiNAC™ Network Access Control Solution

	FNC-CA-500C	FNC-CA-600C	FNC-CA-700C	FNC-M-550C
Type	Mid-range Control and Application Server	High Performance Control and Application Server	Ultra High Performance Control and Application Server	Centralized Management Appliance
Target Environment	Small Environments	Medium Environments	Large Environments with few Persistent Agents	Multi-site environments with multiple appliances
Capacity	Manages up to 1,000 ports in the network*	Manages up to 7,500 ports in the network*	Manages up to 15,000 ports in the network*	Unlimited

Virtual appliances are also available, please refer to www.fortinet.com for more information

FortiSandbox™ Advanced Threat Prevention System

	PAAS FORTISANDBOX CLOUD	FSA-VM	FSA-500F	FSA-1000F/-DC	FSA-2000E	FSA-3000F
Effective Sandboxing Throughput ¹ (Files/Hour)	20 - 4,000	100 - 4,000	500	1,000	1,400	3,700
Number of Users ²	10 - 2,000	50 - 2,000	500	700	1,000	6,000
Number of VMs	up to 200	up to 8	2 + 4 Optional	2 + 12 Optional	4 + 20 Optional	8 + 64 Optional

1. Tested based on files with 80% documents and 20% executables. Includes both Static and Dynamic analysis with pre-filtering enabled.
2. Based on a ratio of 20 files per users on a 10-hour period.

FortiClient™ Advanced Endpoint Security

	Windows	MAC OS X	Linux	Android	iOS	Chromebook
Zero Trust Security (ZTNA) Options	✓	✓	✓	—	—	Partial
Next Generation Endpoint Security (EPP / APT) Options	✓	✓	✓	—	—	—
Cloud Based Endpoint Security (SASE) Options	✓	✓	✓	—	—	—
Security Fabric Components	✓	✓	Partial	Partial	Partial	Partial
VPN Client	✓	✓	SSL VPN only	✓	SSL VPN only	—

FortiMail™ Messaging Security Server

	FML-200F	FML-400F	FML-900F	FML-2000F	FML-3000F	FML-3200E
Email Routing* (Msg/Hr)	50,000	250,000	800,000	1.6 Mil	3.5 Mil	3.4 Mil
Performance Enterprise ATP* (Msg/Hr)	30,000	150,000	400,000	800,000	2.1 Mil	2.0 Mil
Email Domains	20	100	800	1,000	2,000	2,000
Server Mode Mailboxes	150	400	1,500	2,000	3,000	3,000
Storage Capacity	1× 1 TB	2× 1 TB	2× 2 TB (8 TB Max)	2× 2 TB (12 TB Max)	2× 2 TB (20 TB Max)	2× 2 TB (20 TB Max)

* Measured based on 100KB message size, no queuing.
Virtual appliances are also available, please refer to www.fortinet.com for more information

FortiWeb™ Web Application Firewall

	FWB-100E	FWB-400E	FWB-600E	FWB-1000E	FWB-2000F	FWB-3000F	FWB-4000F
Throughput (HTTP)	50 Mbps	250 Mbps	750 Mbps	1.3 Gbps	5 Gbps	10 Gbps	70 Gbps
Total Interfaces	4x GE RJ45	4x GE RJ45 4x GE SFP	2 (+2 bypass) x GE RJ45, 4x GE SFP	2 (+4 bypass) GE RJ45, 4x SFP GE, 2x 10GE SFP+	4x 10GE SFP+, 4x GE RJ45 Bypass, 4x GE SFP	10x 10GE SFP+ (incl. 2 Bypass), 8x GE RJ45 Bypass	2x 40GE QSFP Bypass, 10x 10GE SFP+ (incl. 2 Bypass), 8x GE RJ45 Bypass

Virtual appliances are also available, please refer to www.fortinet.com for more information



Virtual Appliance Support Matrix

	VMWare vSphere	Citrix Xen Server	Xen	KVM	Microsoft Hyper-V	Nutanix AHV	Amazon AWS	Microsoft Azure	Oracle OPC/OCI	Google GCP	Alibaba Aliyun
FortiGate-VM *	•	•	•	•	•	•	• / #	• / #	• /#	• /#	• / #
FortiManager-VM	•	•	•	•	•	•	• / #	•	•	•	•
FortiAnalyzer-VM	•	•	•	•	•	•	• / #	•	•	•	•
FortiWeb-VM	•	•	•	•	•	•	• / #	• / #	•	•	•
FortiWeb Manager-VM	•						•				
FortiMail-VM	•	•		•	•	•	• / #	• / #		•	
FortiAuthenticator-VM	•		•	•	•		•	•	•		
FortiADC-VM	•	•	•	•	•	•	• / #	• / #	• / #	• / #	
FortiVoice-VM	•	•		•	•		•	•			
FortiRecorder-VM	•	•		•	•		#				
FortiSandbox-VM	•			•	•	•	• / #	#			
FortiSIEM-VM	•			•	•	•	•	•			•
FortiProxy-VM	•			•							

*Available as FortiGate-VMX solution for VMware NSX environment, AzureStack and RackSpace (PAYG) # on-demand

List of Other Products

FortiADC Application Delivery Controller
FortiAI Virtual Security Analyst™
FortiCASB Cloud Access Security Broker
FortiCarrier CGN Gateway
FortiCWP Cloud Security Analytics
FortiDDoS DDoS Mitigator
FortiDeceptor Deception-based Solution
FortiEDR EDR Solution

FortiExtender 3G/4G WAN Extender
FortiHypervisor Hybrid Virtual Appliance
FortiInsight UEBA Solution
FortiIsolator Browser Isolation Platform
FortiMonitor NPMD, DEM and IM Systems
FortiProxy Secure Web Gateway
FortiRecorder Network Video Security
FortiSIEM SIEM with UEBA Solution

FortiSOAR SOAR Solution
FortiTester Network Tester
FortiToken 2 Factor Authentication Token
FortiVoice Secure VoIP Solution
FortiWLC Wireless Controller
FortiWLM Wireless Manager
FortiXDR Extended Detection and Response



www.fortinet.com

Copyright © 2022 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.

Fortinet is committed to driving progress and sustainability for all through cybersecurity, with respect for human rights and ethical business practices, making possible a digital world you can always trust. You represent and warrant to Fortinet that you will not use Fortinet's products and services to engage in, or support in any way, violations or abuses of human rights, including those involving censorship, surveillance, detention, or excessive use of force. Users of Fortinet products are required to comply with the Fortinet EULA (<https://www.fortinet.com/content/dam/fortinet/assets/legal/EULA.pdf>) and report any suspected violations of the EULA via the procedures outlined in the Fortinet Whistleblower Policy (https://secure.ethicspoint.com/domain/media/en/gui/19775/Whistleblower_Policy.pdf).